


| | | |
|--|---|---|
| Anziehvorschrift für Zylinderkopf | 144.150 |  |
| Tightening Instructions for Cylinder Head | | |
| Instructions de serrage pour culasse | | |
| Prescripciones de apriete para culatas | | |
| | passend für / suitable for adaptable à / adaptable a | Fiat |
| | | Das Original |

Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete
Tête de vis / Cabeza de tornillo



760.870
M 10 x 85/103



| | | | |
|-------------|---|-------|------------|
| Anziehen/ | * | 20 Nm | M 8: 30 Nm |
| Tightening/ | | 40 Nm | |
| Serrage/ | ➤ | 90° | |
| Apriete | ➤ | 90° | |

Zeichenerklärung / Explanations / Explication / Explicacion

| | | | | |
|---|---|------------------------------|--------------------------------|---------------------------------------|
| * | neue Zylinderkopfschrauben verwenden | use new cylinder head bolts | utiliser des vis neuves | emplar tornillos nuevos |
| ★ | Warmlauf (80°C) | warm up time (80°C) | chauffage (80°C) | calentamiento (80°C) |
| □ | Schrauben einzeln lösen und wieder anziehen | loosen and tighten each bolt | deserrer et serrer vis par vis | aflojar y apretar tornillo a tornillo |
| ● | Setzzeit | relaxation time | durée de tassement | tiempo de espera |
| ➤ | Drehwinkel | torque angle | angle de serrage | ángulo de giro |

Motortyp / Engine type / Type de moteur / Tipo de motor

≙ 1,74/1,65 mm, Ø 87 mm

Mot.: 159 A3.000, 160 E1.011, 220 A2.000
1,6 ltr.

Palio, Punto, Scudo, Tempra, Tipo, Uno
Lancia Dedra, Delta
Peugeot Expert, Citroën Jumpy

ElringKlinger AG, Max-Eyth-Str.2
72581 Dettingen / Erms. Tel. 07123/724 601

144.150