



Stay pumped – all along the journey.

Spare parts for the ContiMobilityKit:
the tyre sealant.

- › Replacement product of original equipment quality “Engineered in Germany”
- › Non-hazardous latex-based tyre sealant
- › Extended shelf life of up to five years
- › Sealant bottle can be disposed of in household waste
- › No need to remove and replace valve core



www.continental-mobility.com



Part number: 17120400000

Extended movability in case of a puncture.

The tyre sealant is pumped by the Continental compressor into the tyre, enabling the onward journey to the nearest garage or tyre service (max. 80 km/h and max. 200 km). It seals car tyre punctures caused by nails or similar objects with a diameter of up to 6 mm.

Product contents:

- › Pressure-resistant 450 ml tyre sealant bottle

Technical specifications of sealant bottle:

Sealant amount	Shelf life	Dimensions
450 ml	5 years	Ø 87 mm × 125 mm
Weight	Application temperature	
585 g	-30°C to +60°C	

Application for passenger car tyres:

The product can be used for the tyre dimensions which are shown in the following chart and with a required tyre pressure of up to 300 kPa (3 bar, 43 psi). 450 ml replacement bottles can be used as a replacement for ContiMobilityKit's 300 ml, 450 ml and 560 ml OE bottles (560 ml OE bottle depending on tyre dimensions - please see chart).

Tyre width in mm	Tyre cross section												Rim size in inches	
130	25-80												R 10	
195													R 14	
135/	25	30	35	40	45	50	55	60	65	70	75	80	R 15	
145/	25	30	35	40	45	50	55	60	65	70	75	80		
155/	25	30	35	40	45	50	55	60	65	70	75	80		
165/	25	30	35	40	45	50	55	60	65	70	75	80		
175/	25	30	35	40	45	50	55	60	65	70	75	80		
185/	25	30	35	40	45	50	55	60	65	70	75	80		
195/	25	30	35	40	45	50	55	60	65	70	75	80		
205/	25	30	35	40	45	50	55	60	65	70	75			
215/	25	30	35	40	45	50	55	60	65	70				
225/	25	30	35	40	45	50	55	60	65					
235/	25	30	35	40	45	50	55	60						
245/	25	30	35	40	45	50	55							
155/	25	30	35	40	45	50	55	60	65	70	75	80		R 16
165/	25	30	35	40	45	50	55	60	65	70	75	80		
175/	25	30	35	40	45	50	55	60	65	70	75	80		
185/	25	30	35	40	45	50	55	60	65	70	75	80		
195/	25	30	35	40	45	50	55	60	65	70	75	80		
205/	25	30	35	40	45	50	55	60	65	70				
215/	25	30	35	40	45	50	55	60	65					
225/	25	30	35	40	45	50	55	60						
235/	25	30	35	40	45	50	55							
245/	25	30	35	40	45	50								
185/	25	30	35	40	45	50	55	60	65	70	75		R 17	
195/	25	30	35	40	45	50	55	60	65	70				
205/	25	30	35	40	45	50	55	60	65					
215/	25	30	35	40	45	50	55	60	65					
225/	25	30	35	40	45	50	55	60						
235/	25	30	35	40	45	50	55							
245/	25	30	35	40	45	50								
255/	25	30	35	40	45									
265/	25	30	35	40										
275/	25	30	35											
285/	25	30	35											

Tyre width in mm	Tyre cross section												Rim size in inches
205/	25	30	35	40	45	50	55	60					R 18
215/	25	30	35	40	45	50	55	60					
225/	25	30	35	40	45	50	55	60					
235/	25	30	35	40	45	50							
245/	25	30	35	40	45								
255/	25	30	35	40	45								
265/	25	30	35	40									R 19
275/	25	30	35										
285/	25	30	35										
295/	25	30											
215/	25	30	35	40	45	50	55						
225/	25	30	35	40	45	50	55						
235/	25	30	35	40	45	50							R 20
245/	25	30	35	40	45								
255/	25	30	35	40									
265/	25	30	35	40									
275/	25	30	35										
225/	25	30	35	40	45								
235/	25	30	35	40	45								
245/	25	30	35	40									
255/	25	30	35										
265/	25	30	35										

Last updated: 02/2016