



<b>Anziehvorschrift für Zylinderkopf</b>	<b>180.770</b>	
<b>Tightening Instructions for Cylinder Head</b>		
<b>Instructions de serrage pour culasse</b>		
<b>Prescripciones de apriete para culatas</b>		
	passend für / suitable for adaptable à / adaptable a	<b>Alfa Romeo</b> Das Original

Schraubenkopf / Head shape  
Tête de vis / Cabeza de tornillo

Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete



152.080  
M10x1,25x254



Anziehen/	*	20 Nm	*	AR 67204 (145/146)
Tightening/		40 Nm		40 Nm
Serrage/	➤	90°	➤	90°
Apriete	➤	90°	➤	90°
	➤	90°	➤	90°

Zeichenerklärung / Explanations / Explication / Explicacion

* *	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
* *	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
□	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro

**Motortyp / Engine type / Type de moteur / Tipo de motor**

145, 146  
GTV, Spider, 155

Mot. AR 67204, AR 16201

1995>1997  
1995>1997

ElringKlinger AG, Max-Eyth-Str.2  
72581 Dettingen / Erms. Tel. 07123/724 601

**\*180.770\***