



| | | |
|--|--|---|
| Anziehvorschrift für Zylinderkopf | 520.800 passend für / suitable for adaptable à / adaptable a FORD |  Das Original |
| Tightening Instructions for Cylinder Head | | |
| Instructions de serrage pour culasse | | |
| Prescripciones de apriete para culatas | | |

Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete
 Tête de vis / Cabeza de tornillo



087.830
 M 10x1,5x143

| | | |
|-------------|---|-------|
| Anziehen/ | * | 15 Nm |
| Tightening/ | | 40 Nm |
| Serrage/ | ➤ | 90° |
| Apriete | | |

Zeichenerklärung / Explanations / Explication / Explicacion

| | | | | |
|---|---|------------------------------|--------------------------------|---------------------------------------|
| * | neue Zylinderkopfschrauben verwenden | use new cylinder head bolts | utiliser des vis neuves | emplar tornillos nuevos |
| ★ | Warmlauf (80°C) | warm up time (80°C) | chauffage (80°C) | calentamiento (80°C) |
| ☐ | Schrauben einzeln lösen und wieder anziehen | loosen and tighten each bolt | deserrer et serrer vis par vis | aflojar y apretar tornillo a tornillo |
| ● | Setzzeit | relaxation time | durée de tassement | tiempo de espera |
| ➤ | Drehwinkel | torque angle | angle de serrage | ángulo de giro |

Motortyp / Engine type / Type de moteur / Tipo de motor

Focus, C-Max ab 09/04>

1,6 Ltr. PFI VCT

| | |
|--|-----------|
| ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601 | *520.800* |
|--|-----------|