



| | | |
|--|---|---|
| Anziehvorschrift für Zylinderkopf | 586.280 |  |
| Tightening Instructions for Cylinder Head | | |
| Instructions de serrage pour culasse | | |
| Prescripciones de apriete para culatas | | |
| | passend für / suitable for adaptable à / adaptable a | Chrysler / Dodge / Fiat |
| | | Das Original |

Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete
Tête de vis / Cabeza de tornillo



949.390
M12x1,5x128



| | | |
|-------------|---|-------------|
| Anziehen/ | * | 30 Nm |
| Tightening/ | | 45 Nm |
| Serrage/ | ➤ | 75° |
| Apriete | ➤ | 50° |
| | ☐ | loosen 360° |
| | | 30 Nm |
| | | 45 Nm |
| | ➤ | 75° |
| | ➤ | 50° |

Zeichenerklärung / Explanations / Explication / Explicacion

| | | | | |
|---|---|------------------------------|--------------------------------|---------------------------------------|
| * | neue Zylinderkopfschrauben verwenden | use new cylinder head bolts | utiliser des vis neuves | emplar tornillos nuevos |
| ★ | Warmlauf (80°C) | warm up time (80°C) | chauffage (80°C) | calentamiento (80°C) |
| ☐ | Schrauben einzeln lösen und wieder anziehen | loosen and tighten each bolt | deserrer et serrer vis par vis | aflojar y apretar tornillo a tornillo |
| ● | Setzzeit | relaxation time | durée de tassement | tiempo de espera |
| ➤ | Drehwinkel | torque angle | angle de serrage | ángulo de giro |

Motortyp / Engine type / Type de moteur / Tipo de motor

Ø: 96 mm; \pm : 0,45 mm
mounting position: right
Mot.: ERB
3,6 Itr. V6

200, 300C, Grand Voyager, Challenger, Charger
Durango, Journey, Freemont,
Grand Cherokee, Wrangler

ElringKlinger AG, Max-Eyth-Str.2
72581 Dettingen / Erms. Tel. 07123/724 601

586.280