

Product information

AIC Germany Gear oil ATF Versatile

AIC No. 74759

Description

Latest generation automatic transmission oil based on HC synthetic base oils. Globally compatible for the requirements of many automatic transmission and vehicle manufacturers. Suitable for use in automatic and manual transmissions, clutch and steering systems, hydraulics and auxiliary drives in passenger cars and commercial vehicles.

Observe the manufacturer's instructions!

AIC Germany also recommends this product for vehicles for which the following specifications are required:

BMW 7045 E / 8072 B / LA 2634 / LT 71141 • Chrysler ATF +3 / ATF +4 • Hyundai SP-III / SP-II • JWS 3309 (Aisin Warner) • Kia SP-II / SP-III • MAN 339 Typ V1 / 339 Typ Z2 / 339 Typ Z1 • Daimler NAG-1 • MB 236.2 / 236.5 / 236.6 / 236.7 / 236.9 / 236.10 / 236.11 / 236.91 • Mitsubishi SP-II • Subaru ATF • Volvo 97341 / 97340 • Voith H55.6335.XX (G 607) • VW G 052 990 / G 055 025 • ZF TE-ML 02F / TE-ML 03D / TE-ML 04D / TE-ML 05L / TE-ML 09 / TE-ML 11A / TE-ML 11B / TE-ML 14A / TE-ML 14B / TE-ML 17C • Toyota Type T-IV / Type T-III • Dexron III H • Mitsubishi SP-III • Mazda ATF M-V / ATF M-III • AE (LT 71141) Nissan AT-Matic D Fluid / AT-Matic J Fluid • Nissan AT-Matic K Fluid • Ford Mercon V • Allison C4 / TES 295 • JASO 1-A • Caterpillar TO-2 • Honda ATF Z1

Characteristic data	Density at 15 °C	0,850 g/cm ³
		DIN 51757
Viscosity at 40 °C	36,4 mm ² /s	
	ASTM D 7042-04	
Viscosity at 100 °C	6,9 mm ² /s	
	ASTM D 7042-04	
Viscosity at -40 °C (Brookfield)	<= 20000	
	ASTM D 2983-09	
Viscosity index	150	
	DIN ISO 2909	
Flash point	230 °C	
	DIN ISO 2592	
Pourpoint	-48 °C	
	DIN ISO 3016	
Colour	red	
Available container	1 l Plastic tin	74759
		D-GB-F-IT-NL-DA-RUS-LT-CZ