

Product information

AIC Germany Gear oil ATF Versatile Low Viscosity

AIC No. 74760

Description

Latest generation automatic transmission oil, globally compatible for the requirements of many automatic transmission and vehicle manufacturers. HC synthetic base oils supplemented with high-performance, modern additives.

Observe the manufacturer's instructions!

AIC Germany also recommends this product for vehicles for which the following specifications are required:

Specifications and approvals
Dexron VI • Ford Mercon LV

Aisin Warner AW-1 • BMW M-1375.4 • Fiat 9.55550-AV5 • JWS 3324 (Aisin Warner) Honda ATF 3.1 • Hyundai SP-IV • Mazda ATF FZ • MB 236.12 • MB 236.14 • Nissan AT-Matic S Fluid • Toyota WS • VW G 055 005 • VW G 055 540 • VW G 060 162

Characteristic data	Density at 15 °C	0,845 g/cm ³
		DIN 51757
Viscosity at 40 °C	28,5 mm ² /s	
	ASTM D 7042-04	
Viscosity at 100 °C	5,8 mm ² /s	
	ASTM D 7042-04	
Viscosity at -40 °C (Brookfield)	≤ 15000 mPas	
	ASTM D 2983-09	
Viscosity index	155	
	DIN ISO 2909	
Flash point	210 °C	
	DIN ISO 2592	
Pourpoint	-48 °C	
	DIN ISO 3016	
Colour	brownish	
Colourindex (ASTM)	4	
	DIN ISO 2049	
Available container	1 l Plastic tin	74760
		D-GB-F-IT-NL-DA-RUS-LT-CZ