



<b>Anziehvorschrift für Zylinderkopf</b>	<b>763.845</b>	 Das Original
<b>Tightening Instructions for Cylinder Head</b>		
<b>Instructions de serrage pour culasse</b>		
<b>Prescripciones de apriete para culatas</b>		
	passend für / suitable for adaptable à / adaptable a	<b>Opel</b>

Schraubenkopf / Head shape      Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete  
Tête de vis / Cabeza de tornillo



Anziehen/ Tightening/ Serrage/ Apriete	<b>A Außentorx</b> > Mot. 14137011 M11x110x1,25 Elring-ZKS 077.890  * 25 Nm ➤ 65° ➤ 65° ➤ 65° ★ 15 min ➤ 30°-45°	<b>B Innentorx</b> Mot. 14137012 > M11x105x1,25 Elring-ZKS 803.010  * 25 Nm ➤ 90° ➤ 90° ➤ 90°
---	--	---

Zeichenerklärung / Explanations / Explication / Explicacion

✳	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
☐	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro

**Motortyp / Engine type / Type de moteur / Tipo de motor**

86 Ø

Mot. 20 XE, C 20 XE, 4 Cyl., 2,0 l (DOHC) 16V

110 kW (150 PS)

Kadett-E 1988>

Vectra 10/1988>

Calibra 09/1989>

ElringKlinger AG, Max-Eyth-Str.2  
72581 Dettingen / Erms. Tel. 07123/724 601

**\*763.845\***