



| | | | |
|--|---|---|--------------|
| Anziehvorschrift für Zylinderkopf | 789.550 |  | |
| Tightening Instructions for Cylinder Head | | | |
| Instructions de serrage pour culasse | | | |
| Prescripciones de apriete para culatas | | | |
| | passend für / suitable for adaptable à / adaptable a | Opel / Suzuki | Das Original |

Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete
Tête de vis / Cabeza de tornillo



| | | |
|---|---|-------------|
| Anziehen/ Tightening/ Serrage/ Apriete | M10 * 20 Nm 40 Nm ➤ 60° ➤ 60° | M8 25 Nm |
|---|---|-------------|

Zeichenerklärung / Explanations / Explication / Explicacion

| | | | | |
|---|---|------------------------------|--------------------------------|---------------------------------------|
| * | neue Zylinderkopfschrauben verwenden | use new cylinder head bolts | utiliser des vis neuves | emplar tornillos nuevos |
| ★ | Warmlauf (80°C) | warm up time (80°C) | chauffage (80°C) | calentamiento (80°C) |
| □ | Schrauben einzeln lösen und wieder anziehen | loosen and tighten each bolt | deserrer et serrer vis par vis | aflojar y apretar tornillo a tornillo |
| ● | Setzzeit | relaxation time | durée de tassement | tiempo de espera |
| ➤ | Drehwinkel | torque angle | angle de serrage | ángulo de giro |

Motortyp / Engine type / Type de moteur / Tipo de motor

1,2 Ltr. 4 Cyl.

Mot. K12B

63 KW (86 PS)

Opel Agila B

Suzuki Splash, Swift IV

ElringKlinger AG, Max-Eyth-Str.2
72581 Dettingen / Erms. Tel. 07123/724 601

789.550