

DONNEES TECHNIQUES

Position	E6 - De la pompe à la crémaillère
Longueur du flexible [mm]	2521
Type connecteur 1	Fileté
Raccord 1	M16x150
Type connecteur 2	Fileté
Raccord 2	M16x150
Position du conducteur	pour véhicule avec direction à gauche
poids [g]	667

PHOTOS



APPLICATIONS

VOLVO		
S60 (00-09) - 2.0 T	180 ch	09.2001 >
S60 (00-09) - 2.4	140 ch	11.2000 >
	170 ch	11.2000 >
S60 (00-09) - 2.4 Bifuel	140 ch	06.2002 >
S60 (00-09) - 2.4 Bifuel (LPG)	140 ch	06.2002 > 04.2010
S60 (00-09) - 2.4 T AWD	200 ch	11.2001 >
S60 (00-09) - 2.5 T	210 ch	02.2004 >
S60 (00-09) - 2.5 T AWD	210 ch	04.2004 >
S80 (99-06) (TS, XY) - 2.0	163 ch	06.1998 > 07.2006
S80 (99-06) (TS, XY) - 2.0 T	180 ch	12.1999 > 07.2006
	226 ch	06.1998 > 07.2006
S80 (99-06) (TS, XY) - 2.4	140 ch	01.1999 > 07.2006
	170 ch	01.1999 > 07.2006
S80 (99-06) (TS, XY) - 2.4 Bifuel (LPG)	140 ch	09.2001 > 07.2006
S80 (99-06) (TS, XY) - 2.4 T	200 ch	06.2000 > 07.2006
S80 (99-06) (TS, XY) - 2.4 T5 AWD	200 ch	04.2000 > 09.2003
V70 (00-07) Break (P2_) - 2.0 T	180 ch	07.2001 >
V70 (00-07) Break (P2_) - 2.4	140 ch	03.2000 >
	170 ch	03.2000 >
V70 (00-07) Break (P2_) - 2.4 Bifuel (LPG)	140 ch	09.2001 > 08.2007
V70 (00-07) Break (P2_) - 2.5 T	209 ch	04.2004 >
V70 (00-07) Break (P2_) - 2.5 T AWD	209 ch	09.2002 >
V70 XC - 2.5 T XC AWD	209 ch	09.2002 >