



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*0622*00

Reason for extension:

SECTION I

0.1. Make (trade name of manufacturer) : Le Rapide

0.2. Type and general commercial description(s) : 025911

0.3. Means of identification of type marked on the : Type approval number

component

0.3.1. Location of that marking : On type plate

0.5. Name and address of manufacturer : Bosal Le Rapide

Rue de Reims

F-51490 Beine Nauroy France

0.7. In the case of components and separate technical: On type plate

units, location and method of

affixing of the EEC type approval mark

0.8. Address(es) of assembly plant(s) : See information document

(annex III, item 0.8)

Type-approval number: e4*94/20*0622*00

SECTION II

1. Additional information (where applicable) See Appendix I

Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76

8218 NX Lelystad

3. Date of test report

Number of test report

5. Remarks (if any)

6. Place

2.

4.

7. Date

8. Signature

22-08-2002

RDW-94/20-4173

See Appendix I

Zoetermeer

22-08-2002

J.P.M. Laumen

- The index to the information package lodged with the competent authority that has granted 9. type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No: e4*94/20*0622*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1	Additional	inform	ation
1.	Additional	шиоп	iauon

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which : See fitting instructions the device is designed or restricted :

1.3. Maximum D-value : 6,46 kN

1.4. Maximum vertical load S at the coupling point : 70 kg

1.5 Maximum load U at the fifth wheel : ---- ton

coupling point

1.6. Maximum V-value : ---- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

: See fitting instructions

1.8 Information on the fitting of special towing brackets or mounting plates

: See fitting instructions

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.

