

NEDERLAND (THE NETHERLANDS)

2 4 JAN 2000



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)



Type-approval number: e4*94/20*1418*00

Reason for extension:

SECTION I

0.1.	Make (trade name of manufacturer)	:	Bosal
0.2.	Type and general commercial description(s)	:	024761
0.3.	Means of identification of type marked on the component	:	Approval number
0.3.1.	Location of that marking	:	On type plate
0.5.	Name and address of manufacturer	:	Bosal postbus 168 4920 AD Made Nederland
0.7.	In the case of components and separate technical units, location and method of affixing of the EEC type approval mark	:	On type plate

Address(es) of assembly plant(s)

: See information document (annex III, item 0.8)

0.8.

Type-approval number: e4*94/20*1418*00

SECTION II

1. Additional information (where applicable) : See Appendix I

Technical service responsible for carrying out : 1

the tests

2.

RDW

Testbaan|Centrum

Talingweg 76 8218 NX Lelystad

3. Date of test report : 08-12-1999

4. Number of test report : RDW-94/20-1065

5. Remarks (if any) : See Appendix I

6. Place : Zoetermeer

7. Date : 300 JAN 2000

8. Signature : Signature

RD

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

A.J. Schullman

Appendix I

to EEC type-approval certificate No: e4*94/20*1418*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1. Additional information

1.1. Class of the type of coupling A50-X

1.2. Categories or types of vehicles for which

the device is designed or restricted

See fitting instructions

1.3. Maximum D-value

1.6.

7,32

kN

1.4. Maximum vertical load S at the coupling point

kg

1.5 Maximum load U at the fifth wheel

ton

coupling point Maximum V-value

kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

See fitting instructions

1.8 Information on the fitting of special towing brackets or mounting plates

: See fitting instructions

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.

