



FLEXIBLE AIR VENT HOSE

PRODUCT TYPE: AIR AND DEFROSTER SYSTEMS

RECOMMENDED FOR: Air connections, defroster ducts and air or heater ducting - use in low pressure air or vacuum applications only.

RESISTANT TO: Resistant to the harmful conditions under the bonnet; heat and oil.

CONSTRUCTION:

- SHAPE:** Straight
- TUBE:** Neoprene
- REINFORCEMENT:** Synthetic
- WIRE:** Metal Wire
- COVER:** Neoprene

STANDARDS:

- SAE NORM** -
- DIN NORM** -

TEMPERATURE:







Gates	PN	↔		⌀	↔	↷	⌚	💣	⊙
		mm	"	mm	m	mm	bar	bar	mm/HG
24300	4663-04108	16	5/8	21	3.048	25	0.7	2.8	127
24301	4663-04109	19	3/4	24	3.048	25	0.7	2.8	127
24302	4663-04110	22	7/8	27	3.048	25	0.7	2.8	127
24303	4663-04111	25	1	30	3.048	25	0.7	2.8	127
24304	4663-04112	32	1 1/4	37	3.048	25	0.7	2.8	127
24305	4663-04113	35	1 3/8	39	3.048	38	0.7	2.8	127
24306	4663-04114	38	1 1/2	43	3.048	38	0.7	2.8	127
24307	4663-04115	42	1 5/8	46	3.048	51	0.7	2.8	127
24308	4663-04116	45	1 3/4	50	3.048	51	0.7	2.8	127
24309	4663-04117	48	1 7/8	53	3.048	51	0.7	2.8	127
24310	4663-04118	50	2	56	3.048	51	0.35	1.4	76
24311	4663-04119	54	2 1/8	59	3.048	64	0.35	1.4	76
24312	4663-04120	57	2 1/4	62	3.048	64	0.35	1.4	76
24313	4663-04121	60	2 3/8	65	3.048	64	0.35	1.4	76
24314	4663-04122	63	2 1/2	69	3.048	64	0.35	1.4	76
24315	4663-04123	67	2 5/8	72	3.048	71	0.35	1.4	76
24316	4663-04124	70	2 3/4	75	3.048	71	0.35	1.4	76
24317	4663-04125	76	3	81	3.048	76	0.35	1.4	76
24318	4663-04126	89	3 1/2	94	3.048	89	0.35	1.4	76
24319	4663-04127	92	3 5/8	97	3.048	102	0.35	1.4	76