


DONNEES TECHNIQUES

Diamètre 1 [mm]	39
matière	caoutchouc
Info complémentaire	Avec mise a l'air/reniflard
Diamètre 2 [mm]	9
Hauteur [mm]	195

PHOTOS



APPLICATIONS

RENAULT		
SAFRANE (92-96) (B54_) - 2.0 (B540)	105 ch	11.1992 > 07.1996
SAFRANE (92-96) (B54_) - 2.0 12V (B542, B54E)	132 ch	04.1992 > 07.1996
SAFRANE (92-96) (B54_) - 2.1 dT (B546)	88 ch	11.1993 > 07.1996
SAFRANE (92-96) (B54_) - 2.2 (B541)	107 ch	04.1992 > 07.1996
SAFRANE (92-96) (B54_) - 2.2 (B543)	137 ch	04.1992 > 07.1996
SAFRANE (92-96) (B54_) - 2.5 dT (B548)	113 ch	12.1992 > 07.1996
SAFRANE (92-96) (B54_) - 3.0	170 ch	02.1993 > 06.1996
SAFRANE (92-96) (B54_) - 3.0 Biturbo 4x4 (B545)	262 ch	02.1993 > 07.1996
SAFRANE (92-96) (B54_) - 3.0 V6 (B54B, B544)	167 ch	12.1992 > 07.1996
SAFRANE (92-96) (B54_) - 3.0 V6 4x4 (B54B, B544)	167 ch	12.1992 > 07.1996
SAFRANE (96-00) (B54_) - 2.0 16V (B54L)	136 ch	07.1996 > 12.2000
SAFRANE (96-00) (B54_) - 2.2 dT (B54G)	113 ch	07.1996 > 12.2000
SAFRANE (96-00) (B54_) - 2.5 20V (B54F)	165 ch	07.1996 > 12.2000
SAFRANE (96-00) (B54_) - 2.9 24V (B54N)	190 ch	03.1999 > 12.2000
SAFRANE (96-00) (B54_) - 3.0 V6	167 ch	07.1996 > 12.2000